

Technical specification

Main Unit	Rated voltage	110V-120V, 50-60Hz
	Rated power	865W
	Water proof	IPX4
	Power cord length	About 2.2m
Toilet	Flush volume	1.6/1.1Gpf, 6.0L(full flush)/4.1L(half flush)
	Flushing mode	Siphonic jet
	Rough-in	305mm
	Outlet outside diameter	≤100mm
	Drainage method	S-trap
	Water pressure range	0.09MPa (dynamic pressure, flow rate of 3.96+Gal/min or 15.0+L/min) - 0.8MPa (static pressure)
Cleaning device	Heating mode	Instant
	Heating power	120V/1400W
	Water temperature	6-level adjustment
	Water volume	3-level adjustment
	Cleaning mode	Rear washing / Oscillating washing, Front washing / Oscillating washing
	Nozzle position	5-level adjustment
	Water pressure protector	Pressure maintaining device, Automatic pressure relief device
	Anti-fouling device	Automatic nozzle cleaning, Anti-syphon device, Anti-backflow device, Filter device
	Safety device	Thermal fuse, Water temperature sensor, Ground protection, Thermostat, Leakage protection plug, Over temperature protection

Drying device	Warm air volume	Over 0.2m ³ /min	
	Warm air temperature	6-level adjustment	
	Heating power	250W	
	Safety device	Thermal fuse, Temperature sensor, Thermostat	
Deodorization	Deodorization method	Photocatalyst-free	
Heated seat	Surface temperature	6-level adjustment	
	Heating power	50W	
	Burn protection	After 10 minutes of use, the seat temperature will automatically drop slowly to a low level	
	Safety device	Seat sensor, Temperature sensor, Thermal fuse, Leakage protection plug, Thermostat	
Caring device	Night light assembly	Intelligent, Always on, Always off	
	User ID setting	To avoid interference when used by multiple users	
	Automatic flushing	Automatic flushing after use	
	Power off flush (optional)	Toilet will be washed manually after power failure (This function is optional, please install the battery before use when it is available.)	
	Foot sensor flushing function (optional)	Foot sensor flushing	
Difference description	Lid opening	Soft close	Lid auto-open
		Antibacterial site	
		Seat, Nozzle	

Rated power: Under the condition of ambient temperature 23°C/73°F, water static pressure 0.18MPa±0.02MPa, water temperature 15°C/59°F, power toilet on, set water pressure, seat temperature, water temperature to the highest level in turn and perform one rear washing cycle.